#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 26 May 2005 (26.05.2005)

**PCT** 

## (10) International Publication Number WO 2005/047706 A1

(51) International Patent Classification<sup>7</sup>: 29/00

F04C 18/16,

(21) International Application Number:

PCT/GB2004/004660

(22) International Filing Date:

4 November 2004 (04.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


0326061.9 10 November 2003 (10.11.2003) GB 0405317.9 9 March 2004 (09.03.2004) GB 0406142.0 18 March 2004 (18.03.2004) GB

(71) Applicant (for all designated States except US): THE BOC GROUP PLC [GB/GB]; Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TUNNA, Clive, Marcus, Lloyd [GB/GB]; BOC Edwards, Manor Royal, Crawley, West Sussex RH10 9NH (GB). McDIARMID, Allan, Edmiston [GB/GB]; Boc Edwards, Unit 2, Dolphin Road, Shoreham by Sea, West Sussex BN43 6PY (GB). TOMKINS, Mark, Edward [GB/GB]; BOC Edwards, Unit 6, Malthouse Trading Estate, Brighton Road, Shoreham by Sea, West Sussex BN43 6RJ (GB).
- (74) Agent: BOOTH, Andrew, Steven; The BOC Group Plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: IMPROVEMENTS IN DRY PUMPS



(57) Abstract: A screw pump comprises a pair of rotors (92, 94) each carrying an external screw thread (96, 98), the pair of rotors being rotatably mounted in a stator (72) and arranged such that, in operation, the screw threads of the rotors intermesh as the rotors rotate in opposing directions. Means (100, 102) are provided for actively controlling the axial position of the rotors within the stator during use of the pump.

WO 2005/047706 A1

### WO 2005/047706 A1



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.